

## Type SPE-SS Load Cell



### Short Description



- Stainless Steel IP67/68 single point load cell
- Colorless anodized
- Suitable for pricing scales, bench scales, etc.
- Maximum platform size: 600 x 600 mm
- A 1000 Ohm type available (R1) but is excluded from OIML



Test certificate no. TC7868 Revision 1  
C of C no R60/2000-NL1-12.52



Certificate no. 11-062

### Available Models

P/N	Capacity	Accuracy	Full Article Description
27058781-1	100kg	C3/C4	SPE-SS-C3/C4-100kg-3G
27058781-2	200kg	C3/C4	SPE-SS-C3/C4-200kg-3G
27058781-3	350kg	C3/C4	SPE-SS-C3/C4-350kg-3G
27058781-4	500kg	C3/C4	SPE-SS-C3/C4-500kg-3G

## Type SPE-SS Load Cell

### Technical Specifications SPE-SS


Accuracy Class		OIML R60 C3	OIML R60 C4	OIML R60 C5
Output Sensitivity ( = FS )	mV/V	2.0 ± 0.2		
Maximum Capacity ( Emax )	kg	100, 200, 350, 500		
Max. Number of Load Cell Intervals	nLc	3000	4000	5000
Ratio of min. LC Verification Interval	Y = Emax / vmin	10000	15000	20000
Combined Error	%FS	≤± 0.0230	≤± 0.0175	≤± 0.0140
Minimum dead load	Of Emax	0%		
Safe overload	of Emax	150 %		
Ultimate overload	of Emax	300 %		
Zero balance	of FS	< ± 2.0 %		
Excitation, recommended voltage	V	5 ~ 12		
Excitation maximum	V	18		
Input resistance	Ω	390 ± 15		
Output resistance	Ω	350 ± 5		
Insulation resistance	MΩ	≥5000 ( at 50VDC )		
Compensated temperature	°C	-10 ~ +40		
Operating temperature	°C	-35 ~ +65		
Storage temperature	°C	-40 ~ +70		
Element material		Stainless Steel		
Ingress Protection (acc. to EN 60529)		IP67/68		
Recommended torque on fixation bolts	Nm	M8:10		

### Wiring

#### Features:

Shielded, 4 conductor cable.  
 Cable diameter: Ø5.6mm.  
 Standard cable length: 3m.  
 Shield connected to element.  
 Cable jacket in PVC.

#### Mode of Connection



## Type SPE-SS Load Cell

Dimensions in mm

